

Multi Acoustic Roll.

March 2025 | Data Sheet



Description.

Superglass Multi Acoustic Roll is a non-combustible glass mineral wool insulation roll. The flexible roll is partially perforated at 2x600mm and 3x400mm widths to allow friction fitting between common stud/joist spacings, minimising gaps at joints and reducing on-site cutting & waste.

Application.

Superglass Multi Acoustic Roll is designed to provide both thermal and acoustic insulation for various applications, including:

- Internal walls and floors
- Timber and metal stud partitions
- Separating walls and floors
- Drylining system

Performance.

Density:

Manufactured at a minimum density of 10kg/m³.

Thermal Conductivity:

Declared thermal conductivity (lambda (λ) value) of 0.044W/mK.

Fire Classification:

Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to BS EN 13501-1:2018 Reaction to Fire.



Typical applications:
Internal walls and floors.



Acoustic
Insulation



Thermal
Insulation



Non-
combustible



Recycled
Glass Content

Intelligent Environments
Superglass
superglass.co.uk

Multi Acoustic Roll.

Technical Characteristics.

Product Specification.

Thickness (mm)	Length (m)	Width (mm)	Pack Area (m ²)	Packs per pallet	Thermal Conductivity (W/mK)	Thermal Resistance (m ² K/W)	Product Code
60	11.25	1200/2x600/3x400	13.500	24	0.044	1.35	2144295
75	10.50	1200/2x600/3x400	12.600	24	0.044	1.70	2144388
80	10.40	1200/2x600/3x400	12.480	24	0.044	1.80	2144296
100	10.10	1200/2x600/3x400	12.120	24	0.044	2.25	2144294

Please note that all dimensions are nominal.

Additional Information.

Vapour Resistivity.

The product has a nominal vapour resistivity of 5 MNs/gm.

Environmental Credentials.

- Our products and their pallets are wrapped in low-density polyethylene (LDPE4) plastic, which contains a minimum 30% recycled material and is fully recyclable. Before recycling, please consult your local authority for guidance.
- ISO 14001:2015 – Environmental Management Systems (EMS) certified. Certificate number: EMS 646508.
- Contains no ozone-depleting substances or greenhouse gases.
- Manufactured from up to 84% recycled glass.
- Generic BRE Green Guide Rating of A+.

For more information, please refer to the Environmental Product Declaration (EPD).

Standards and Approvals.

Manufactured in accordance with:

- BS EN 13162:2012+A1:2015 Thermal insulation products for buildings - Factory made mineral wool (MW) products.
- BS EN 13172: 2012 Thermal insulation products - Evaluation of conformity.
- ISO 9001:2015 – Quality Management Systems (QMS). Certificate number: FM 02264.

Certifications.

- UKCA certified to BS EN 13162:2012+A1:2015. Certificate number: 0086 CPR 469699.
- CE marked to EN 13162:2012+A1:2015. Certificate number: 0751-CPR-399.0-01.
- CCPI (Code for Construction Products Information) Assessment Mark. Certificate number: 005800127/0227.

A copy of the product Declaration of Performance (DoP) can be downloaded from the Superglass website.

EUCEB (European Certification Board of Mineral Wool Products).

All Superglass glass mineral wool products are made of non-classified fibres and are certified by EUCEB. EUCEB is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008. Certificate number: BEUC-511-27949-491-14462.

Handling & Storage.

The product should be stored properly and handled in such a way as to ensure that the product remains clean and undamaged.

The product is supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors, or under a waterproof covering and off the ground to protect from weather damage. The product should not be left permanently exposed to the elements.

All Superglass products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fungi.

Intelligent Environments
Superglass

UK
CA

CE

ISO 14001:2015
Environmental
Management

ISO 9001
Quality
Management

BRE Global
Verified
EPD

MADE IN
BRITAIN

NBS Source
PARTNER

EUCEB

Etex UK Insulation Ltd | Thistle Industrial Estate | Kerse Road | Stirling | FK7 7QQ | UK

MAR05
March 2025

Technical

Hotline: 0808 1645 134
Email: technical.stirling@etexgroup.com

Customer Services

Tel: 01786 451170
Email: customerservice.stirling@etexgroup.com

Social

✉ superglass_uk
in [superglassuk/](https://www.linkedin.com/company/superglassuk/)
f [superglassinsulationuk](https://www.facebook.com/superglassinsulationuk)