

PRODUCT DATA

Revision 6.5

itpltd.com

FLAMEOUT® BREATHE membrane is breathable, non-woven fabrics with superior self-extinguishing, flame retardant properties, available in two grades of FR rating. It is independently tested to EN 13501-1 and is suitable for wall and roof installations.

SAFE ONE® is the UK's first non-combustible breather membrane, independently tested to EN 13501-1 with the highest W1 water resistance. It is suitable for closed and open high rise façades.

STAMISOL® A1 is a new non-combustible breather membrane, independently tested to EN 13501-1 with a W2 water resistance.

FLAMEOUT® VCLs are polyethylene-based vapour control membranes with a reinforcement scrim to provide sufficient tensile strength in wall and roof insulations.

FLAMEOUT® BLOCK CLASS A is a non-combustible vapour barrier which is independently tested to EN 13501-1. It is a glass woven scrim with an aluminium layer which is protected against corrosion with a special lacquer. This vapour barrier is specifically suitable for 11+m high rise buildings. They are independently tested to British and international flame retardant standards. Air and Vapour Control Layers (AVCLs) ensure that the building envelope is properly sealed to control ventilation and prevent heat loss in compliance with Building Regulations Part L. Installed on the warm side of insulation, AVCLs protect insulates from interstitial condensation.

PRODUCT	Flame Retardant EN 13501-1	Colour	Application	Weight EN 1849-2 gsm	Tensile strength EN 12311-1 N/50mm	Temperature range °C	Water vapour resistance EN ISO 12572	Water vapour transmission	Resistance to Penetration of Air EN 12114 m³ (m²/h/50Pa)	Water tightness EN 1928 (A) Class	Sizes metres	Roll weight kg	Pallet quantity
NONCOMBUSTIBLE & FLAME RETARDANT BREATHER MEMBRANES FOR WALL & ROOF INSTALLATIONS													
FlameOut Breathe	Class B-s1,d0	Dark Grey	NA	90	MD 170 XD 140	-40/ +70	0.1 MN/g	Sd 0.02m EN ISO 12572 BS 4016 Class 1	<0.1	W1	1.5 x 50 3.0 x 50	7.2 14.0	28 28
Safe One (SF400)*	Class A2-s1,d0	Black	Openings <50mm Overall exposure ≤50% of the surface area	310	MD 1400 XD 1400	-30/+250	0.6 MN/g	Sd 0.12m EN ISO 12572	<0.009	W1	2.65 x 20	18.0	25
Stamisol A1	Class A1	Milky White	For use behind closed façades or rainscreens	260	MD 1600 XD 2000	-30/+250	0.5 MN/g	Sd 0.1m EN ISO 12572	-	W2	2.65 x 30	22.0	-
FLAME RETARDANT VAPOUR CONTROL LAYERS FOR WALL & ROOF INSTALLATIONS													
FlameOut Block Standard	Class B-s1,d0	Milky White	NA	140	MD>500 XD>500	-40/+70	140 MN/g	Sd 28mEN 1931 1.56 g/m²/day BS 3177	0.002	W1	2 x 50	14.5	52
FlameOut Block Premium	Class B-s1,d0	Milky White	NA	210	MD>500 XD>500	-40/+70	300 MN/g	Sd 60m EN 1931 0.77 g/m²/day BS 3177	NA	W1	2 x 50	21.5	46
FlameOut Block Class A**	A2-s1,d0	White/ Silver	NA	155	MD>1,200 XD >1,000	-40/+100	20,000 MN/g	Sd 4,000m	N/A	W1	1.5 x 50	13.5	27

NOTE: As per EN 13859-2, Clause 5.2.2, in the case of the breather membrane or VCL being used on a supporting structure, further flame retardant testing of the structure may be needed to determine the flame retardancy of the construction due to a possible different flame retardancy of the supporting construction materials itself (e.g. wood). Safe One is Class A2-s1,d0 when free hanging or directly installed on a supporting substructure with a flame retardant classification of A1 or A2. FlameOut Breathe FR is Class B-s1,d0 when free hanging or directly installed on a supporting substructure with a flame retardant classification of A1 or A2. FlameOut Breathe has been tested directly installed onto wood as Class D-s1,d0. FlameOut Block FR and FlameOut Block FR Plus are Class B-s1,d0 when free hanging or directly installed on a supporting substructure with a flame retardant classification of A1 or A2. ***Important:** Register your warranty with ITP prior to installation. Separately provided Installation instructions provided by the Safe One Technical Team must be complied with to validate any warranty. Safe One proprietary adhesives, tapes and accessories must be used to validate any warranty. **** Reflectivity to ASTM C 1371-04a: 100%**

FlameOut® is a registered trademark of Industrial Textiles & Plastics Ltd. E&OE.

© Industrial Textiles & Plastics Ltd



Industrial Textiles & Plastics Ltd
Stillington Road, Easingwold, York YO61 3FA
United Kingdom

Telephone: +44 (0)1347 825200
Email: info@itpltd.com
Website: www.itpltd.com



DISCLAIMER OF EXPRESS AND IMPLIED WARRANTIES

Subject to the limitations, disclaimers and statements as set forth below, Industrial Textiles & Plastics Ltd represents to the Buyer that the product or products delivered to the Buyer conform(s) to the manufacturer's description and specifications attached to or delivered with the product.

The representation that Industrial Textiles & Plastics Ltd makes to the Buyer that the product or products conform(s) to the manufacturer's description and specifications applies only under such circumstances when the Buyer utilises the product or products as specified and under normal use for which said product was intended.

Any alleged nonconformity shall be made in writing to Industrial Textiles & Plastics Ltd specifically stating and describing any such alleged nonconformity.

The representation by Industrial Textiles & Plastics Ltd that the product or products delivered to the Buyer conform(s) to the manufacturer's description and specification as attached to or delivered with the product is expressly in lieu of all other representations, warranties, expressed or implied, and of all other obligations and liabilities, including consequential damages, on the part of Industrial Textiles & Plastics Ltd. Industrial Textiles & Plastics Ltd neither assumes nor authorises any person to assume for it any other liability in connection with the sale of the product.

The representation of conformity by Industrial Textiles & Plastics Ltd as represented by Industrial Textiles & Plastics Ltd shall in addition to the above be null and void in the event that the product is misused or handled in a negligent manner by Buyer or any third party.

Industrial Textiles & Plastics Ltd shall not be liable for damages or delays, if such occur, on account of defective material or workmanship or delays in shipment, nor will any allowances be granted for any repairs, alterations, work done or expense incurred in connection with any repairs, alterations or replacements except on specific written authority by Industrial Textiles & Plastics Ltd.

Industrial Textiles & Plastics Ltd shall in no way be liable or responsible for injuries or damages to persons or property arising out of the use or operation of the product as herein contemplated, and Buyer hereby agrees to indemnify and save harmless Industrial Textiles & Plastics Ltd from all such liability and responsibility.

Industrial Textiles & Plastics Ltd shall not be liable for any consequential damages for any reason including but not limited to those contemplated herein and whether such consequential damages may have been foreseeable, proximately caused or otherwise occurring.

Due to a policy of continued research and development, Industrial Textiles & Plastics Ltd reserves the right to alter specifications without notice. Products are offered subject to our normal Conditions of Sale, which are available on request.

Samples and specifications are of an illustrative nature and supplied free of charge. They do not form part of any contract or any intended contract with the user. Final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user and the user must assume all risk and liability in connection therewith.

This disclaimer of Express or Implied Warranties constitutes a significant limitation on the rights and remedies otherwise available to the Buyer, which the Buyer freely and voluntarily acknowledges and accepts as part of the consideration for the contract to purchase the product or products from Industrial Textiles & Plastics Ltd.

Test Results are obtained under laboratory conditions on new material and not under actual usage conditions. Test results only relate to the sample tested. No warranties or assurances of reliability, suitability or fitness for a particular purpose of specimens or data are offered. Assessment of suitability of such material and data for intended use is the sole responsibility of the customer.