

WOOD SURVEY FORM

*1 Wood Derivative e.g. MDF, OSB Cross Laminated Timber. *2 Previously Coated e.g. Tantalised or Waterproofed. *3 Beams What is above e.g. Room, Loft, Roof. *4 Cladding Type e.g. Tongue & Groove, Feather Edge, Solid. *5 What is behind e.g. Blockwork, Plasterboard, Cement Board. *6 Flooring Type e.g. Tongue & Groove, Solid. *7 Flooring Underside what is Above e.g. concrete, Further wooden flooring.

Customer Name								
Customer Contact Details								
Merchant Supplier and Branch								
Site Address								
Protection Required (For Doors see Separate Sheet)								
30 Minutes		60 Minutes						
Class 1		Class 0		Class B		Class C		
Is the protection for								
Your Own Safety	Required for Building Regulations							
About the Wood								
Softwood		Hardwood		Rough Sawn Open Grained				
Planed		Plywood		Wood Derivative Please specify *1				
Previously Coated With								
Nothing		Painted		Clear Finish		Stained Finish		Other Please specify *2
Type of Finish Required								
Painted		Clear Finish		Stained Finish		Natural		
Colour Required								
Is the Project								
Internal		External						
Beams or Joists								
Depth & Width		What is above *3						
Cladding or Panelling								
Type *4 and Thickness and What is Behind *5								
Flooring Underside								
Type *6 and Thickness and what is Above *7								
Total Area to Protect								

NOTES:

To help us provide the correct specification and certification please complete as much detail as possible. If you have different levels of protection please complete an enquiry for each. Please note that Class 1, 0, B, C are not the same as 30 and 60 minutes fire resistance.

 01142 768008

 thermoguard.co.uk

 technical@thermoguard.co.uk





Door			
What is the measurement for the thickest part of the door			mm
What is the measurement of the thinnest part (panel) of the door			mm
How is the door glazed			
Is there an intumescent strip	In the door	In the frame	
Surrounding Frame and Wall			
Has the wall been assessed for Fire Resistance			
Has the door frame been assessed for Fire Resistance			
Is the required compartmentation 30 or 60 minutes			
How is the wall constructed			
Concrete	Dry Lining		
Brick	Lath & Plaster		
Total Number of Doors (Complete a separate form for each different type of door)			
Survey Completed By			
Company Name			
Specification Issued By			
Specification Date			
Specifications are valid for 6 months from the specification date.			
Specification Number			

DOORS

It is important to note that most modern internal doors cannot be upgraded to achieve 30 minutes Fire Resistance.

However, where installation of fire rated door sets is not an option due to listed building status or similar Thermoguard Timbercoat Insulating Basecoat and Thermoguard 2K Fire Varnish Basecoat with the correct topcoat are capable of upgrading doors under specific circumstances.

- Doors would be that can afford to lose 2mm to charring and
- Solid, joint-free doors with compressed core and a reasonable thickness (6 mm +), veneer faces bonded to either side of the core. These can be flush doors or pressed to create a moulded look.
- Well-seasoned, old or sturdy doors with 35mm + thick frames and panels 10mm + thick.

If you are unsure if your doors fulfil this criteria complete this form and return to Thermoguard Technical on technical@thermoguard.co.uk or call 01142 768008 Option 2 to discuss your project

**Contact information submitted will
only be used for the purposes of
specification and certification.**

 01142 768008

 thermoguard.co.uk

 technical@thermoguard.co.uk

