

PROCHECK 300

PROCHECK 300

Product specification to be Procheck 300 by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Vapour Control Layer to be used shall be Procheck 300 supplied by The A Proctor Group, Blairgowrie.
 Procheck 300 is a reinforced polyethylene vapour control layer (VCL) used for vapour control and airtightness.

Product

Product performance specification as follows:

Thickness

0.3mm

Roll Size

2m x 50m

Material

Reinforced polyethylene

Certification

Minimum required: Not Applicable

Technical Properties - according to standard BS EN 13984:2013

- Mass per Unit area: to be no less than 151g/m²
- Water Vapour Resistance: to be no less than Sd 64m when tested to EN1931
- Tensile Strength: to be no less than MD 230N/50mm; CD 130N/50mm when tested to EN 12311-1
- Nail Tear Resistance: to be no less than MD 100N; CD 125N when tested to EN 12310-1
- Elongation: to be no greater than MD 20% and CD 20% when tested to EN 12311-1

Procheck 300 is a reinforced, polyethylene vapour control layer for use within roof and wall constructions to prevent warm, moist air escaping from inside the building and condensing within the insulation. The woven, polypropylene, multifilament scrim reinforcement provides resistance to tears and punctures to withstand tough site conditions and is unaffected by chlorine. Procheck 300's vapour resistance of Sd 64m makes it the ideal choice for applications such as heated warehouses, schools and shops. Its translucent colour allows visibility to the substructure

Benefits

- Suitable for low risk applications e.g. heated warehouses
- Minimal tears due to reinforcement
- Visibility to substructure for ease of installation

Product Reference [Procheck 300](#)

Issue Date: July 2025
 Version: 1.006
 New Review Due: July 2026

