

# FramePro® WI

## DESCRIPTION

FramePro WI is a vapour permeable, airtight wall underlay, which is flexible allowing for simple installation. FramePro WI is water resistant to class WI and has a resilient composition, which resists punctures and tears during installation.

FramePro WI can be utilised with Wraptite Tape to provide a simplified method of achieving low air leakage rates, particularly when installed on site, as is typical with large scale rain screen construction, or when sealing junctions between prefabricated building components. By reducing the likelihood of failures to meet designed airtight levels, FramePro WI helps ensure “as designed” performance is achieved. This helps to narrow the performance gap between as designed and actual energy performance. FramePro WI is designed to cost effectively replace conventional breather membranes whilst increasing airtightness.

## KEY BENEFITS

- Increased airtightness over traditional breather membranes
- Allows temporary protection until primary external covering is installed / applied
- Provides a reduced risk of tears and subsequent remedial work
- Airtight and vapour permeable
- BBA Certificate No. 24/7182



Property	Test Method	Mean Results	
	<b>BS EN 13859-2:2010</b>		
Roll sizes	-	1.5m x 50m	
Thickness	-	0.4mm	
Mass per unit area	EN 1849-2	100 g/m <sup>2</sup>	
Reaction to Fire	EN 11925-2	Class E	
Water vapour resistance	EN 12572	Sd 0.02m	
Water Penetration	EN 1928	Class WI (before ageing) Class WI (after ageing)	
Tensile Strength	EN 12311-1	MD 240N MD 200N	CD 125N (before ageing) CD 110N (after ageing)
Tear Resistance	EN 12310-1	MD 100N	CD 120N
Elongation	EN 12311-1	MD 60% MD 50%	CD 70% (before ageing) CD 90% (after ageing)



Revised: July 2025

Version: 1.008

Next review due: July 2026



Download a brochure from our website...

[www.proctorgroup.com](http://www.proctorgroup.com)

contact@proctorgroup.com | +44 (0) 1250 872261

**Proctor**  
Group