

PROFLOOR SOLO BATTENS

PROFLOOR SOLO BATTENS

Product specification to be Profloor Solo Battens by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Acoustic Floating Floor System to be used shall be Profloor Solo Battens supplied by The A Proctor Group, Blairgowrie. Profloor Solo Batten comprises a dressed softwood timber batten, with an integral closed cell resilient layer to provide impact sound reduction in separating floors.

Product

Product performance specification as follows:

Standard Battens

Nominal height (uncompressed) 40 or 52mm
 Width 45mm
 Length 2.4m

Material

Closed cell polyolefin foam bonded to timber battens

Accessories

Flanking Strip: 5mm x 50, 75, 100, 125 or 150mm x 10m
 Profloor Adhesive: 1 litre bottles

Certification

Minimum required: The timber should be responsibly sourced, being FSC sourced.

Technical Properties

- Resilient Layer Composition: to be single layer closed cell foams
- Compression under normal loadings: to be no more than 1-2mm
- RD Compliance: FFT3 for 52mm battens
- Refurb Compliance: suitable for improving the impact sound reduction between existing separating floors
- Timber or Concrete Floor: to be suitable for use in concrete floors

Profloor Solo Batten System is specified and detailed similar to a standard batten for the purpose of supporting the chosen floor finish, but has the advantage of providing effective isolation of the floor finish from the structure.

Benefits

- Reduces impact and airborne noise pollution in multi - level buildings
- Improves both airborne and impact sound performance
- MR, impregnated battens are available
- Available in 40mm & 52mm overall depths
- Cost effective batten system that complies with FFT 3
- Floors can be used immediately after installation

Product Reference [Profloor Solo Battens](#)

Revision Date: March 2025

Version: 1.002

New Review Due: March 2026