



- Robust and abrasion resistant surface
- Efficient installation with two-way integrated self-adhesive strips and verified system accessories
- Can be exposed to the weather for 4 weeks

Packaging

Roll width [m]	Roll length [m]	Roll area [m ²]	Roll weight [kg]
1,5	50	75	13

Characteristics

Material	multi-layer composite of PP fleece with polyolefin and copolymer coating	
Thickness [mm]	0,50	
Water vapour diffusion equivalent [m]	2	
Water vapour diffusion resistance [μ]	4000	
Mass [g/m ²]	170	
Watertightness [kPa]	≥ 2	
Temperature resistance [°C]	-40 to +80	
Minimum application temperature [°C]	0	
Reaction to fire (EN 13501-1)	E	
Tensile strenght [N/5 cm]	longitudinal	230
	transversal	170
Elongation at maximum tensile strength [%]	longitudinal	50
	transversal	40
Resistance to tearing (nail shank) [N]	longitudinal	135
	transversal	175

Product description

PAVATEX DSB 2 is used as an airtight vapour control on roof sheathing for over-rafter insulation with PAVATEX soft woodfibre boards. The longitudinal joints are sealed with the integrated self-adhesive strips. The transversal joints, the connections and the penetrations are sealed using PAVATEX sealing products. If mechanically secured, PAVATEX DSB 2 can be left exposed to the weather for 4 weeks. Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Storage

Store cool and dry, lying down or upright, protected from sunlight and humidity.

