



## KlasseCLOTH™ S10 Duct Tape

### Description:

PE-coated cloth backing, combined with a high performance rubber-resin adhesive coating.

### Application:

Primarily designed for sealing double-glazed units, this versatile tape can also be used for bundling, heavy carton packing, general maintenance, pipe wrapping, carpet fixing, air-conditioning duct seams and other joint sealing.

### Features:

Enjoys high tensile strength, excellent moisture resistant and easy tear. Also conforms well to irregular surfaces.

### Product Specifications:

Backing: Cloth backing 27 Mesh

Adhesive: Rubber-resin

Thickness: 0.15mm  $\pm$ 10%

### Shelf life:

To obtain best performance, use this product within one year from date of manufacture and store in the original carton under normal conditions of 75°F (25°C) and 50% ~ 65% R.H.

Typical Physical Properties		Test Method
Peel Adhesion	16N/25mm	PSTC-1
Rolling Tack (11mm ball)	5 cm	PSTC-6
Holding Power	1,000+ Min	PSTC-7
Service Temperature Range	-20 ~ +80°C	-

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because Klasse cannot accept responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.