



## Adhesive Specialities Ltd

Tickitape House, 31 Bone Lane Newbury  
Berkshire RG14 5SH  
Tel: +44 (0)1635 49825  
Fax: +44 (0)1635 45768

Email: [info@tickitape.co.uk](mailto:info@tickitape.co.uk)  
Website: [www.tickitape.co.uk](http://www.tickitape.co.uk)

# TECHNICAL DATA SHEET

10/1/14

**REF:** AS217SH - Standard Cloth Tape

**DESCRIP:** A synthetic rubber based cloth tape with a flexible, easily mouldable and waterproof PE coated fabric which is tearable by hand. The tape has a strong initial tack and an excellent adhesive power.

<b>SPEC:</b>	<u>Width:</u>	48, 50, 72 mm & others upon request
	<u>Length of Rolls:</u>	50M & others upon request
	<u>Thickness:</u>	175 $\mu$ m
	<u>Adhesive</u>	Hot melt/synthetic rubber
	<u>Carrier:</u>	PE coated fabric
	<u>Mesh Density:</u>	26
	<u>Adhesion to steel plate (N/ 2.5 cm)</u>	23
	<u>Rolling Ball Tack (cm):</u>	< 3
	<u>Tensile Strength (N/25mm):</u>	95
	<u>Service Temperature (°C)</u>	-10C° to +75°

**STORAGE** Store in a cool dry place away from sunlight and direct heat sources. Maximum storage period 12 months.

**USES:** The tape is perfectly suitable for adhesion on smooth and rough surfaces such as stainless steel, polyethylene, glass and wood is used for general applications such as repairing, sealing, holding, protecting and bundling. .

**APPLICATION:** Prior to use carefully check that the contact surfaces are totally dry and clean from all traces of oil, grease and dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.