

Product Drawing




- Bus Wire
- Polymeric Heating Element
- Primary Insulation
- Earthing
- Outer Jacket

- Nickel Plated Copper Wire
- Polyolefin + C/B
- FR Polyolefin
- Braided Tinned Copper Wire Nickel
- PE + C/B FR Polyolefin (-P)
- PVDF(-F)

Power Output Graph

Thermal output ratings on insulated metal pipe



Circuit Breaker Selection

Max. circuit length(m) at 230Vac based on starting temp. (°C) and typical Type C circuit breaker size (Amps).

Product code \ Breaker Size(A)	Start-up Temp. -20°C						Start-up Temp. 0°C						Start-up Temp. 10°C					
	10A	16A	20A	25A	32A	40A	10A	16A	20A	25A	32A	40A	10A	16A	20A	25A	32A	40A
HSR102-CP(F)	84	134	155	155	155	155	101	162	169	169	169	169	131	193	193	193	193	193
HSR162-CP(F)	59	94	118	129	129	129	71	113	141	142	142	142	92	147	162	162	162	162
HSR242-CP(F)	42	67	84	104	111	111	36	57	71	89	114	117	50	81	101	126	126	126
HSR302-CP(F)	32	51	64	80	101	101	32	51	64	80	102	113	41	66	82	102	124	124