MuteMat® 2 Product Data

Description: MuteMat® 2 is two-ply, high performing resilient floor mat

achieving a superior impact attenuation in both timber and concrete structures, as well as high mass to reduce airborne noise which is suitable for all building types. MuteMat® 2 comprises of two materials, a 6mm PE crosslinked foam (closed-cell) which is in contact with the surface, and a 7.5kg

per m2 Mass Loaded Vinyl.

Dimensions: 10mm x 1200mm x 1200mm

 Sheet Size:
 1.44 m2

 Mass:
 8.3 kg/m2

 Sheet Weight:
 12 kg

Features and Benefits: 2 laminated layers of 7.5kg/m2 MLV, 6mm Closed-Cell Foam.80%

Recycled and 100% Recyclable.

Mould, moisture and fungus resistant.

Consistent closed cell foam (unlike chip foam).

Performance: Untreated Structure: Ln,w 78dB

 $\begin{array}{lll} \mbox{Treated Structure:} & \mbox{Ln,w 48dB} \\ \mbox{Reduction:} & \Delta \mbox{Lw 30dB} \\ \mbox{Field Test:} & \mbox{L'nT,w 48dB} \\ \end{array}$

Performance will vary with different structural make-up.

Please see performance data for examples.



