

PART REF: SP-GCT-50 (SOLAS420) - Glass Fibre Cloth Tape Class H.

DESCRIPTION: A glass cloth tape coated with a high performance silicone adhesive. It is tough, abrasion resistant and highly conformable with excellent mechanical and electrical properties.



SPECIFICATION:	<u>Width:</u>	12mm (others available)
	<u>Standard Length:</u>	25m & 50m (others available)
	<u>Total Thickness:</u>	18µm
	<u>Tensile Strength:</u>	60kg / 25mm
	<u>Elongation:</u>	5%
	<u>Steel Adhesion:</u>	560g / 25mm
	<u>Dielectric strength:</u>	3000V
	<u>Application Temperature:</u>	-20°C to +180°C.
	<u>Class:</u>	H (UL H/200)

STORAGE: The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

USES: Transforms outer insulation. Coil end fixing. Layer insulation.

APPLICATION: Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.